Data sheet

valid from: 7/18/24





Type 3519 Flow Wet-Tap Valve

Flow:

- Installs into pipe sizes: DN15 to DN900, 0.5 to 36 in
- Material: PVC body, seals FKM or EPDM
- Max Pressure rating: 7 bar @ 20 °C, (100 psi @68 °F)
- Standard: FKM O-rings (EPDM or FFKM on request)
- Other materials of rotor and axis on request

MFR #	Description	Pipe Size (inch)	Code
3-3519	Wet-Tap Valve only	-.0	**159 000 757**
P51530-P3	Polypro extended length paddlewheel sensor	0.5 - 4.0	**198 840 310**
3-2536-P3	Polypro extended length low flow paddlewheel sensor	0.5 - 4.0	**159 000 758**
P51530-P4	Polypro extended length paddlewheel sensor	5.0 - 8.0	**198 840 311**
3-2536-P4	Polypro extended length low flow paddlewheel sensor	5.0 - 8.0	**159 000 759**
P51530-P5	Polypro extended length paddlewheel sensor	10.0 - 36.0	**198 840 312**
3-2536-P5	Polypro extended length low flow paddlewheel sensor	10.0 - 36.0	**159 000 760**

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: http://www.gfps.com