



Type 2250 For Level and Depth Control
1/2 inch male union connector

Temperature/Pressure:

- Cable Length: 10 m (32.8 ft)
- Operating Temperature: ** 15° to 85°C (5° to 185°F)
- Operating Pressures:** -XU Ultra Low: 0 to 0.7 bar (0 to 10 psi) -XL Low: 0 to 3.4 bar (0 to 50 psi)
- Compatibility: 8900, 9900 and 9950

Body	Process Connection	Communication Interface	Electrical connection	Cable length (m)	MFR #
PVDF	Thread	S3L	Fixed cable	10	3-2250-11L
PVDF	Thread	S3L	Fixed cable	10	3-2250-11U
PVDF	Thread	4-20 mA	Fixed cable	10	3-2250-21U
PVDF	Thread	4-20 mA	Fixed cable	10	3-2250-21L
PVDF	Thread	S3L	Fixed cable	10	3-2250-11U-1
PVDF	Thread	S3L	Fixed cable	10	3-2250-11L-1
PVDF	Thread	4-20 mA	Fixed cable	10	3-2250-21U-1
PVDF	Thread	4-20 mA	Fixed cable	10	3-2250-21L-1

Output	Connection	Maximum Operation	Code
Digital (S3L)	NPT	3.4 bar (50 psi); 35.15 m (115 ft)	159 001 241
Digital (S3L)	NPT	0.7 bar (10 psi); 7.03 m (23 ft)	159 001 242
4-20 mA	NPT	0.7 bar (10 psi); 7.03 m (23 ft)	159 001 248
4-20 mA	NPT	3.4 bar (50 psi); 35.15 m (115 ft)	159 001 247
Digital (S3L)	ISO	0.7 bar (10 psi); 7.03 m (23 ft)	159 001 478
Digital (S3L)	ISO	3.4 bar (50 psi); 35.15 m (115 ft)	159 001 479
4-20 mA	ISO	0.7 bar (10 psi); 7.03 m (23 ft)	159 001 482
4-20 mA	ISO	3.4 bar (50 psi); 35.15 m (115 ft)	159 001 483

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>