



9900 SmartPro<sup>®</sup> Transmitter

Instruments:

- Large auto-sensing backlit display with at-a-glance visibility
- "Dial-type" digital bar graph
- Optional field upgradable relays
- Custom 13-character label capabilities for the channel type
- Intuitive and "user-friendly" interface consistent with legacy Signet ProPoint<sup>®</sup> and ProcessPro<sup>®</sup> devices

| MFR #     | Inputs                                    | Output     | Communica-<br>tion Interface | Voltage    | Description      |
|-----------|-------------------------------------------|------------|------------------------------|------------|------------------|
| 3-9900-1P | One input: Fre-<br>quency, S3L,<br>4-20mA | One 4-20mA | Analog 4-20<br>mA            | 12 - 24VDC | 9900 Panel Mount |
| 3-9900-1  | One input: Fre-<br>quency, S3L,<br>4-20mA | One 4-20mA | Analog 4-20<br>mA            | 12 - 24VDC | 9900 Field Mount |

Code

159 001 695

159 001 696

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guar-  
anteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail:  
info.ps@georgfischer.comInternet: <http://www.gfps.com>