



## Type 2775/2777 DryLoc ORP Electrodes

### pH/ORP:

- Wetted Materials: Ryton, PTFE, FKM, glass
- Connection: Durable DryLoc® with fold plated connections
- Compatible Preamp/Sensor Electronics: 2750 and 2760
- Compatible Instruments: Use the 2760 preamplifier with the Signet 8750; Use the 2750 sensor electronics with the Signet 8900 or the 9900 Transmitter
- Additional Features: Quick temperature response and can be mounted upside-down
- In-line Mounting styles: Use the sensors 3/4 inch thread to mount to any in-line tee
- Submersible mounting: Available using the back of the preamplifier or sensor electronics
- Applications: Water treatment, water quality monitoring, some harsh chemicals

	MFR #	Style	Compatible Preamplifier	Mounting	Code
*	3-2775	Flat	2750, 2760 DryLoc	with threaded connection	<b>159 000 957</b>
*	3-2777	Bulb	2750, 2760 DryLoc	with threaded connection	<b>159 000 961</b>

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com) Internet: <http://www.gfps.com>