
Data sheet

valid from: 7/11/23



Type 2000 Micro-Flow

Flow:

- Installs into pipe sizes: 0.25 NPT or ISO7/1-R1/4 Threads
- Operating range:0.11 to12.11lpm, 0.03 to 3.2 U.S. gpm
- Max Pressure rating: 0 °C to 80 °C 5.5 bar, 32 °F to 176 °F at 80 psi max
- Power source: 5 to 24V DC @ 10mA
- Compatibility: 8900, 9900, 9900-1BC, 9950

MFR #	Body	Process Connection	Communication Interface	Operating Range	Description
3-2000-11	PPS	Thread	Open Collector Frequency	0.11 to 2.61 lpm	0.25 NPT threads
3-2000-12	PPS	Thread	Open Collector Frequency	0.11 to 2.61 lpm	ISO 7/1-R1/4 threads
3-2000-21	PPS	Thread	Open Collector Frequency	1.13 to 12.11 lpm	0.25 NPT threads
3-2000-22	PPS	Thread	Open Collector Frequency	1.13 to 12.11 lpm	ISO 7/1-R1/4 threads

MFR #	Flow Range (l/min)	Code
3-2000-11	0 - 3	**198 822 000**
3-2000-12	0 - 3	**198 822 001**
3-2000-21	1 - 12	**198 822 002**
3-2000-22	1 - 12	**198 822 003**

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: http://www.gfps.com