

Data sheet

valid from: 7/18/24



Type 2540 Stainless Steel Hot Tap

Flow:

- Installs into pipe sizes: DN40 to DN 900, 1.5 in. to 36 in.
- Operating range: 0.1 to 6 m/s, 0.3 to 20 ft/s
- Max Pressure rating: 17 bar @ 100 °C, 250 psi @ 212 °F Optional EPDM: 17 bar @ 82 °C, 250 psi @ 180 °F
- Power source: 5 to 24V DC, 1.5mA max
- Compatibility: 8900, 9900, 9900-1BC, 9950
- *Recommended 198 820 008 (3-1500.663) Hot Tap installation tool (sold separately)

MFR #	Body	Rotor Pin	Pin	Mounting	Sensor Type
3-2540-3	Stainless steel	Tungsten Carb.	Tungsten Carbide	1.5 in. NPT thread	Remote Mount
3-2540-4	Stainless steel	Tungsten Carb.	Tungsten Carbide	1.5 in. ISO thread	Remote Mount
3-2540-3S	Stainless steel	Stainless Steel	Stainless steel	1.5 in. NPT thread	Remote Mount
3-2540-4S	Stainless steel	Stainless Steel	Stainless steel	1.5 in. ISO thread	Remote Mount

MFR #	Code
3-2540-3	198 840 037
3-2540-4	198 840 038
3-2540-3S	159 001 503
3-2540-4S	159 001 504

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>