



Carbon Steel Threaded Tees with NPT Thread

- PVDF insert - all sizes
- For use with SCH 40 metal pipe (ASTM)
- PTFE tapewetted material. Consult factory for available options.

Type	Size (inch)	L (inch)	H (inch)	Sensor Type	Part No.	weight (kg)
CS4T005	0.50	3.60	4.00	Flow -X0, pH -XX	198 801 459	0.500
CS4T007	0.75	3.60	4.20	Flow -X0, pH -XX	198 801 460	0.500
CS4T010	1.00	3.60	4.20	Flow -X0, pH -XX	198 801 461	0.500
CS4T012	1.25	3.80	4.50	Flow -X0, pH -XX	198 801 462	1.070
CS4T015	1.50	4.10	4.80	Flow -X0, pH -XX	198 801 419	0.610
CS4T020	2.00	4.90	5.30	Flow -X0, pH -XX	198 801 463	0.800

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>