



CUSTOMER

Certificate of Compliance

X-SPY Polyurethane

DESCRIPTION	YES	NO	NA
ISO 9001:2015 QMS		✓	
FDA 21 CFR 177.2800 (TEXTILES)			✓
FDA 21 CFR 177.2600 (RUBBER ARTICLES)			✓
FDA 21 CFR 177.1680 (POLYURETHANE)	✓		
CALIFORNIA PROPOSITION 65			✓
REACH			✓
RoHS			✓
EC1935/2004			✓
EC2023/2006	✓		
EC10/2011			✓
EU DIRECTIVE 2014/34 (ATEX)			✓
PHthalate / BPA FREE	✓		
TSE / BSE / ADI FREE	✓		
LATEX RUBBER FREE			✓
CONTAINS 3TG MINERALS		✓	

X-SPY BetterBalls	XSPY
X-SPY Custom Connector	040XSPY
X-SPY Film	040XSPY
Abrasion-Resistance	Excellent
Temperature Range	0° - 180°F / -53° - 82°C
Durometer (Shore A)	90 +/- 5
Ultimate Elongation	590%
Tensile Strength	3900 PSI
Specific Gravity	2.132 (1mm)
X-Ray/Metal Detectable	Yes
Magnet Susceptible	Yes
Material Thickness	.040" (1mm)

I do hereby certify that the products and/or services supplied on the above referenced invoice number are of the quality specified and conform to all requirements of the purchase order, including quality control, design and material specifications, drawings, packaging, marking and physical identification requirements as well as regulatory requirements as indicated above.

Steven E. Weil

President