



Type 2551 Magmeter, Display Version no Relays Frequency or Digital (S³L) output

Flow:

- Installs into pipe sizes: DN15 to DN900, 0.5 to 36 in
- Operating range: 0.05 to 10 m/s, 0.15 to 33 ft/s
- Max Pressure rating: PP 10.3 bar @ 25 °C, 150 psi @ 77 °F
- Power Source: Frequency: 5 to 24 VDC, 15 mA max. Digital (S³L): 5 to 6.5 VDC, 15 mA max.
- Compatibility: 8900, 9900, 9900-1BC, 9950
- *Only Signet installation fittings
- Standard: FKM O-rings (EPDM or FFKM on request)

MFR #	Body	Electrode	Communication Interface	Sensor Type	Pipe Size (inch)	Code
3-2551-P0-41	PP	316L SS	Freq / Digital S ³ L	Integral Mount	0.5 - 4.0	159 001 261
3-2551-P1-41	PP	316L SS	Freq / Digital S ³ L	Integral Mount	5.0 - 8.0	159 001 262
3-2551-P2-41	PP	316L SS	Freq / Digital S ³ L	Integral Mount	10.0 - 36.0	159 001 432
3-2551-T0-41	PVDF	Titanium	Freq / Digital S ³ L	Integral Mount	0.5 - 4.0	159 001 433
3-2551-T1-41	PVDF	Titanium	Freq / Digital S ³ L	Integral Mount	5.0 - 8.0	159 001 434
3-2551-T2-41	PVDF	Titanium	Freq / Digital S ³ L	Integral Mount	10.0 - 36.0	159 001 460
3-2551-V0-41	PVDF	Hastelloy C	Freq / Digital S ³ L	Integral Mount	0.5 - 4.0	159 001 263
3-2551-V1-41	PVDF	Hastelloy C	Freq / Digital S ³ L	Integral Mount	5.0 - 8.0	159 001 264
3-2551-V2-41	PVDF	Hastelloy C	Freq / Digital S ³ L	Integral Mount	10.0 - 36.0	159 001 462

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>