



Type 2551 Magmeter; Blind Version

Flow:

- Installs into pipe sizes: DN15 to DN900, 0.5 to 36 in
- Operating range: 0.05 to 10 m/s, 0.15 to 33 ft/s
- Max Pressure rating: PP 10.3 bar @ 25 °C, 150 psi @ 77 °F
- Power source: 4 to 20 mA: 21.6 to 26.4 VDC, 21.1 mA max
- *Only Signet installation fittings
- Standard: FKM O-rings (EPDM or FFKM on request)

MFR #	Body	Electrode	Communication Interface	Sensor Type	Pipe Size (inch)	Code
3-2551-P0-12	PP	316L SS	4-20 mA	Integral Mount	0.5 - 4.0	159 001 110
3-2551-P1-12	PP	316L SS	4-20 mA	Integral Mount	5.0 - 8.0	159 001 111
3-2551-P2-12	PP	316L SS	4-20 mA	Integral Mount	10.0 - 36.0	159 001 112
3-2551-T0-12	PVDF	Titanium	4-20 mA	Integral Mount	0.5 - 4.0	159 001 113
3-2551-T1-12	PVDF	Titanium	4-20 mA	Integral Mount	5.0 - 8.0	159 001 114
3-2551-T2-12	PVDF	Titanium	4-20 mA	Integral Mount	10.0 - 36.0	159 001 449
3-2551-V0-12	PVDF	Hastelloy C	4-20 mA	Integral Mount	0.5 - 4.0	159 001 259
3-2551-V1-12	PVDF	Hastelloy C	4-20 mA	Integral Mount	5.0 - 8.0	159 001 260
3-2551-V2-12	PVDF	Hastelloy C	4-20 mA	Integral Mount	10.0 - 36.0	159 001 451

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>