



## Type 2551 Magmeter; Blind Version Frequency or Digital (S<sup>3</sup>L) output

### Flow:

- Installs into pipe sizes: DN15 to DN900, 0.5 to 36 in
- Operating range: 0.05 to 10 m/s, 0.15 to 33 ft/s
- Max Pressure rating: PP 10.3 bar @ 25 °C, 150 psi @ 77 °F
- Power Source: Frequency: 5 to 24 VDC, 15 mA max. Digital (S<sup>3</sup>L): 5 to 6.5 VDC, 15 mA max.
- Compatibility: 8900, 9900, 9900-1BC, 9950
- \*Only Signet installation fittings
- Standard: FKM O-rings (EPDM or FFKM on request)

MFR #	Body	Grounding Ring Material	Communication Interface	Sensor Type	Pipe Size (inch)	Code
3-2551-P0-11	PP	316L Stainless Steel	Freq / Digital S <sup>3</sup> L	-X0	0.5 - 4.0	159 001 105
3-2551-P1-11	PP	316L Stainless Steel	Freq / Digital S <sup>3</sup> L	-X1	5.0 - 8.0	159 001 106
3-2551-P2-11	PP	316L Stainless Steel	Freq / Digital S <sup>3</sup> L	-X2	10.0 - 36.0	159 001 107
3-2551-T0-11	PVDF	Titanium	Freq / Digital S <sup>3</sup> L	-X0	0.5 - 4.0	159 001 108
3-2551-T1-11	PVDF	Titanium	Freq / Digital S <sup>3</sup> L	-X1	5.0 - 8.0	159 001 109
3-2551-T2-11	PVDF	Titanium	Freq / Digital S <sup>3</sup> L	-X2	10.0 - 36.0	159 001 448
3-2551-V0-11	PVDF	Hastelloy-C	Freq / Digital S <sup>3</sup> L	-X0	0.5 - 4.0	159 001 257
3-2551-V1-11	PVDF	Hastelloy-C	Freq / Digital S <sup>3</sup> L	-X1	5.0 - 8.0	159 001 258
3-2551-V2-11	PVDF	Hastelloy-C	Freq / Digital S <sup>3</sup> L	-X2	10.0 - 36.0	159 001 450

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>