Data sheet

valid from: 7/18/24



8059 External Relay Modules

Instruments:

- Relay Outputs: 2 or 4 external contact relays. SPDT 250VAC/30VDC/5A
- Operating Temperature: -10°C to 55°C (14°F to 131°F)
- Relative Humidity: 0 to 90% (non-condensing)
- Pass-through Output: S3L signals can be passed through this unit
- Material: Enclosure: Noryl® UL 94 V-0
- Compatible Instruments: 8900 (S3L Instruments only)

MFR #	Description	Inputs	Voltage
3-8059-4	Four external dry-contact relays	12/24 VDC	12/24 VDC
3-8059-4AC	Four external dry-contact relays with power supply	110/240 VAC	110/240 VAC

MFR #	Code	weight (kg)
3-8059-4	**159 000 772**	0.332
3-8059-4AC	**159 000 773**	0.370

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: http://www.gfps.com