



Type 2536 Rotor-X

Wet-Tap Mount Paddlewheel (use with type 3519 wet tap valve)

Flow:

- Operating range: 0.1 to 6 m/s, 0.3 to 20 ft/s
- Installs into pipe sizes: DN15 to DN900, 0.5 to 36 in
- Max Pressure rating: PP 12.5 bar @ 20 °C, 180 psi @ 68 °F PVDF 14 bar @ 20 °C, 200 psi @ 68 °F
- Power source: <20mA @ 3.3 to 24 VDC
- Compatibility: 8900, 9900, 9900-1BC, 9950
- *Only Signet installation fittings
- Rotor: PVDF
- Open collector output

MFR #	Body	Rotor Pin	Pin	Pipe Size (inch)	DN-DN (mm)	Sensor Type	Code
3-2536-P3	PP	Black PVDF	Titanium	0.5 - 4.0	15-100	Remote Mount	159 000 758
3-2536-P4	PP	Black PVDF	Titanium	5.0 - 8.0	125-200	Remote Mount	159 000 759
3-2536-P5	PP	Black PVDF	Titanium	10.0 - 36.0	250-900	Remote Mount	159 000 760

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>