



## Type 2552 Magmeter Frequency or Digital (S<sup>3</sup>L) output

### Flow:

- Installs into pipe sizes: 2 to 102in, DN50 to DN250
- Operating range: 0.05 to 10 m/s, 0.15 to 33 ft/s
- Max Pressure rating: PP 10.3 bar @ 25 °C, 150 psi @ 77 °F
- Power source: 5 to 26.4 VDC, 15mA max
- O-rings: FKM
- Compatibility: 8900, 9900, 9900-1BC, 9950

MFR #	Body	Electrode	Sensor Type	Mounting	Connection
3-2552-21-A-11	Stainless steel	316 SS	Remote Mount	9.4 in. depth	1 1/4 in. NPT
3-2552-21-B-11	Stainless steel	316 SS	Remote Mount	9.4 in. depth	1 1/4 in. NPT
3-2552-22-A-11	Stainless steel	316 SS	Remote Mount	9.4 in. depth	1 1/4 in. ISO
3-2552-22-B-11	Stainless steel	316 SS	Remote Mount	9.4 in. depth	1 1/4 in. ISO
3-2552-33-A-11	Stainless steel	316 SS	Remote Mount	14.8 in depth	1 1/2 in. NPT
3-2552-33-B-11	Stainless steel	316 SS	Remote Mount	14.8 in depth	1 1/2 in. NPT
3-2552-34-A-11	Stainless steel	316 SS	Remote Mount	14.8 in depth	1 1/2 in. ISO
3-2552-34-B-11	Stainless steel	316 SS	Remote Mount	14.8 in depth	1 1/2 in. ISO

### Code

159 001 513

159 001 515

159 001 517

159 001 519

159 001 521

159 001 523

159 001 522

159 001 524

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:  
info.ps@georgfischer.com Internet: <http://www.gfps.com>