



## Type 2764/2766 DryLoc pH Electrodes

### pH/ORP:

- Wetted Materials: Ryton, PTFE, FKM, carbon graphite, glass
- Connection: Durable DryLoc® with fold plated connections
- Compatible Preamp/Sensor Electronics: 2750 and 2760
- Compatible Instruments: Use the 2760 preamplifier with the Signet 8750; Use the 2750 sensor electronics with the Signet 8900 or the 9900 Transmitter
- Additional Features: Differential reference for additional protection in harsh chemicals; also quick temperature response
- In-line Mounting styles: Use the sensors 1 inch thread to mount to any in-line tee
- Submersible mounting: Available using the back of the preamplifier or sensor electronics
- Applications: Water treatment, water quality monitoring, scrubbers, heavy metal removal, harsh chemicals, etc.

	MFR #	Style	Compatible Preamplifier	Mounting	Code
*	3-2764-1	Flat	2760 DryLoc	with threaded connection	<b>159 000 943</b>
*	3-2764-2	Flat	2750 DryLoc	with threaded connection	<b>159 000 944</b>
*	3-2766-1	Bulb	2760 DryLoc	with threaded connection	<b>159 000 949</b>
*	3-2766-2	Bulb	2750 DryLoc	with threaded connection	<b>159 000 950</b>

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>